



Spray Plaster

May 2008

Readymix Plasters

Knauf Readymix Plasters are a rapid, cost-effective alternative to traditional plaster for finishing walls and ceilings. They are purpose designed for machine application on fast-track building projects. Supplied pre-mixed to the correct consistency for spray application, the finished surfaces can be emulsion painted after only 24 - 48 hrs. So fast that up to 1,000m² per week can be finished by a three man gang.

Technical Service

Hotline: 01795 416 259

Email: technical@knauf.co.uk

Website: www.knaufdrywall.co.uk



Customer Service

Freephone: 0800 521 050

Freefax: 0800 521 205

Email: cservice@knauf.co.uk

Knauf Drywall

PO Box 133

Sittingbourne

Kent ME10 3HW

Tel: 01795 424 499

Fax 01795 428 651

Spray Plaster

May 2008

Key Features

- Fast applied system - up to 1,000m² per week can be finished by a three man gang
- Can be decorated after only 24 - 48 hours
- Can be applied by the same teams applying paint finishes
- Different finishes available: flat & smooth, textured, leathered, combed or rolled
- 9 - 12 month shelf life if stored above 5°C and out of direct sunlight

When to use

- Thin joint block systems, pre-cast panels, Aircrete panels, concrete, brickwork, composite boards and for refurbishment over previously decorated surfaces

Available in

- 25kg bags

Coverage

- Knauf Plano 1.75kg per m² at 1mm thickness
- Knauf Deco 15-18 m² per bag
- Knauf Airless 18-20 m² per bag

Readymix Plasters

Purpose designed for spray application

3 products complete the range: Knauf Plano, Knauf Deco and Knauf Airless

Knauf Plano: Filler and levelling compound for use over thin joint block systems, uneven in-situ concrete and on refurbishment projects to fill cracks, holes and undulations to prepare surface for final decoration. Applied up to 4mm thick in one application. 2 coats are recommended with 12 - 24 hrs drying between applications. Applied using rotary screw worm pump machines. Article Code: 140 04 400

Knauf Deco: Use as a 1 - 2mm top coat on Knauf Plano or as a 2 coat finish directly onto smooth backgrounds including pre-cast panels, Aircrete panels, composite boards, and/or refurbishment over previously decorated surfaces. Applied using rotary screw worm pump machines. Article Code: 140 05 500

Knauf Airless: For use in the same areas as Knauf Deco but applied with an airless high pressure piston pump machine. Article Code: 140 06 600

Other benefits:

- Only 1% waste produced - all material trowelled from surface can be re-applied.
- Plastic bags and shrink-wrap can be recycled.
- Water-based product, non-damaging to health or the environment.
- Flexible products - less likely to crack than plaster skim coats.
- Non-reactive with all substrates including lime plasters and sand and cement renders.
- Offers moisture resistance so suitable for kitchens, bathrooms and changing areas.

Important: After application of plaster it is very important to ventilate to assist drying.