

Product Data Sheet

Knauf Easy Plaster



Knauf Easy Plaster is a ready-mixed lightweight patching plaster specially designed for small to large repairs to cracks in walls and ceilings. Ideal for filling holes up to 40mm deep with a 2 coat application. The plaster can be painted or wallpapered once dry.

Areas of Application

Cracks in walls and ceilings up to 40mm deep. Can be used over plaster, internal renders, brick and stone.

Key Benefits

- Low shrinkage/cracking
- Fills holes up to 40mm deep with a 2 coat application
- Provides a hard surface that can be painted

Technical information

Colour	Size (L)	Coverage	Material Number
Grey	2.5	0.75m ² per litre at 6mm thickness	282344
Grey	6	0.75m ² per litre at 6mm thickness	282343

Sustainability

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Storage and Handling

Avoid contact with skin and eyes. Do not smoke, eat or drink in areas of storage or use. Keep container closed when not in use. Store between 5°C and 25°C in a cool, dry, well-ventilated place. Protect from frost. Keep out of reach of children. Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

Packaging

Recycled content plastic tub. Recyclable at the end of its life.

Shelf Life/Service Life

12 months.

Disposal/Repair

Do not allow to enter drains or water courses. Waste should be disposed of in accordance with the environmental protection act.

Health & Safety

Impermeable protective gloves, safety glasses with side shields due to splashing, and a dust mask when sanding are recommended. For full information, please refer to the safety data sheet.

Application / Installation

Open the tub and stir well, apply evenly to a clean, dry and dust free surface using a trowel or spatula. Use a clean finishing trowel or spatula to smooth over to a flat surface finish. Drying time approximately 24 hours. If required lightly sand with a fine to medium grade sandpaper for a smooth finish.

Drying time is approximately 24 hours dependent on ventilation and humidity, based on 2-4mm application. Applying at different thicknesses will result in a longer drying time.

Additional Documentation

[Safety Data Sheet](#)



Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

0800 521050 (option 2)
Live Webchat 09:00 -17:00
technical-uk@knauf.com

Website

www.knauf.co.uk
www.knauf.ie

Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

KML100449

The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued.

© Copyright Knauf 2023

Creation Date: 25/10/2023
Revision Reference: 001
Revision Date: 25/10/2023